

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the present application:

### **Listing of Claims:**

1. (currently amended) A method for providing position assist information from a base station, comprising:

receiving GPS satellite information at the base station from a GPS satellite;  
transmitting, from the base station, the received GPS satellite information to a GPS enabled device at a time that is not associated with a position request;  
receiving, from the GPS enabled device, decoded position information requiring at least some processing to determine a position of the GPS enabled device from the GPS enabled device; and  
~~determining a position of the GPS enabled device based on the received decoded position information, and transmitting the determined position to the GPS enabled device~~ transmitting, from the base station to the GPS enabled device, the position of the GPS enabled device based on the decoded position information.

2. (previously presented) The method of claim 1, wherein the GPS satellite information is transmitted periodically.

3. (original) The method of claim 1, further comprising periodically locating GPS satellites, wherein the GPS satellites information is periodically received from the located GPS satellites.

4. (original) The method of claim 3, further comprising processing the received GPS satellite information and transmitting the processed information to the GPS enabled device.

5. (currently amended) The method of claim 1, further comprising ~~periodically receiving the GPS satellites information from a position determination entity~~ determining, at the base station, the position of the GPS enabled device based on the decoded position information.

6. (original) The method of claim 1, further comprising transmitting the information to the GPS enabled device each time the GPS enabled device registers with the base station.

7. (original) The method of claim 1, wherein the transmitted information includes access assist information.

8. (original) The method of claim 1, wherein the transmitted information includes sensitivity assist information.

9. (cancelled)

10. (cancelled)

11. (previously presented) The method of claim 1, further comprising:  
    sending the decoded position information to a position determination entity;  
    receiving a position of the GPS enabled device determined from the decoded position information from the position determination entity; and  
    transmitting the position to the GPS enabled device.

12. (currently amended) A method for receiving position assist information from a base station, comprising:  
    receiving GPS satellite information from the base station at a time that is not associated with a position request;  
    storing the received GPS satellite information;  
    receiving the position request;

automatically acquiring GPS satellites using the stored information in response to the received position request;

receiving position information from the acquired GPS satellites;

decoding the received position information to generate decoded position information that requires processing to determine a position;

transmitting the decoded position information to the base station; and

receiving a position determined from the decoded position information from the base station.

13. (original) The method of claim 12, wherein the GPS satellite information is received periodically.

14. (original) The method of claim 12, further comprising registering with the base station, and receiving the GPS satellite information during the registration.

15. (original) The method of claim 12, further comprising receiving position information from the acquired GPS satellites, and determining a position based on the received position information.

16. (cancelled)

17. (original) The method of claim 12, further comprising adjusting a correlation time based on the stored information in order to improve the chances of acquiring the GPS satellites.

18. (original) The method of claim 12, wherein the received information includes access assist information.

19. (original) The method of claim 12, wherein the received information includes sensitivity assist information.

20. (currently amended) A base station, comprising:

a GPS receiver configured to locate, and receive information from, GPS satellites;

a transmitter configured to transmit the received GPS satellite information to a GPS enabled device at a time that is not associated with a position request;

a receiver, ~~the receiver~~ configured to receive decoded position information from the GPS enabled device; and

wherein the base station is configured to determine a position of the GPS enabled device based on the received decoded position information, and to transmit the determined position to the GPS enabled device.

21. (original) The base station of claim 20, wherein the GPS receiver is configured to locate the GPS satellites periodically.

22. (original) The base station of claim 20, further comprising a processor configured to process the received GPS satellite information, wherein the transmitter is configured to transmit the processed information to the GPS enabled devices.

23. (original) The base station of claim 20, further comprising a network interface configured to interface the base station with a position determination entity, wherein the base station is configured to receive GPS satellites information from the position determination entity through the network interface.

24. (original) The base station of claim 20, further comprising a receiver configured to receive registration requests from the GPS enabled device, wherein the base station is configured to transmit the GPS satellite information in response to the registration request.

25. (original) The base station of claim 20, wherein the transmitted information includes access assist information.

26. (original) The base station of claim 20, wherein the transmitted information includes sensitivity assist information.

27. (cancelled)

28. (cancelled)

29. (previously presented) The base station of claim 20, further comprising a position determination entity, wherein the position determination entity is configured to determine the position from the decoded position information.

30. (previously presented) The base station of claim 20, further comprising a network interface configured to interface the base station with a position determination entity, the base station configured to:

send the decoded position information to the position determination entity through the network interface;

receive a position of the GPS enabled device determined from the decoded position information from the position determination entity through the network interface; and

transmit the position to the GPS enabled device.

31. (original) The base station of claim 20, wherein the transmitter is configured to transmit the received GPS satellite information to the GPS enabled device over a control channel.

32. (original) The base station of claim 31, wherein the control channel is a PCS common control channel.

33. (currently amended) A base station, comprising:

a network interface configured to interface the base station with a position determination entity, the base station configured to receive GPS satellite information from the position determination entity;

a transmitter configured to transmit the received GPS satellite information to a GPS enabled device at a time that is not associated with a position request; and

a receiver, ~~the receiver~~ configured to receive decoded position information from the GPS enabled device, the decoded position information requiring processing to determine a position.

34. (original) The base station of claim 33, further configured to receive the GPS satellite information periodically or aperiodically.

35. (original) The base station of claim 33, further comprising a processor configured to process the received GPS satellite information, wherein the transmitter is configured to transmit the processed information to the GPS enabled device.

36. (original) The base station of claim 33, further comprising a receiver configured to periodically receive registration requests from the GPS enabled device, wherein the base station is configured to transmit the GPS satellite information in response to the registration requests.

37. (original) The base station of claim 33, wherein the transmitted information includes access assist information.

38. (original) The base station of claim 33, wherein the transmitted information includes sensitivity assist information.

39. (cancelled)

40. (previously presented) The base station of claim 33 , further configured to:

send the decoded position information to the position determination entity through the network interface;

receive a position of the GPS enabled device determined from the decoded position information from the position determination entity through the network interface; and

transmit the position to the GPS enabled device.

41. (original) The base station of claim 33, wherein the transmitter is configured to transmit the received GPS satellite information to the GPS enabled device over a control channel.

42. (original) The base station of claim 41, wherein the control channel is a PCS common control channel.

43. (currently amended) A GPS enabled device, comprising:

a receiver configured to receive GPS satellite information from a base station at a time that is not associated with a position request;

a memory configured to store the received GPS satellite information;

a GPS receiver configured to, in response to the position request, automatically acquire GPS satellites using the stored GPS satellite information ~~in response to the position request~~, receive position information from the acquired GPS satellites and decode the received satellite information to generate decoded position information that requires processing to determine a position; and

~~a transmitter, wherein the GPS receiver is further configured to receive position information from the acquired GPS satellites and to decode the received satellite information, and wherein the GPS enabled device is further configured to transmit the decoded position information to the base station; and wherein the GPS enabled device is~~, the receiver further configured to receive a the position determined from the decoded position information from the base station.

44. (previously presented) The GPS enabled device of claim 43, further comprising a transmitter, wherein the GPS enabled device is configured to transmit a registration request to the base station using the transmitter, and wherein the GPS satellite information is received during the registration.

45. (cancelled)

46. (original) The GPS enabled device of claim 43, further configured to adjust a correlation time based on the stored information in order to improve the chances of acquiring the GPS satellites.

47. (cancelled)

48. (cancelled)

49. (original) The GPS enabled device of claim 43, further configured to receive the GPS satellite information from the base station over a control channel.

50. (original) The GPS enabled device of claim 49, wherein the control channel is a PCS common control channel.

51. (currently amended) A wireless communication system, comprising:

- a base station, comprising a transmitter configured to transmit GPS satellite information; and

- a GPS enabled device, comprising:

- a receiver configured to receive the GPS satellite information from the base station at a time that is not associated with a position request;

- a memory device configured to store the received GPS satellite information;

- a GPS receiver configured to in response to the position request, automatically acquire GPS satellites using the stored GPS satellite information in



~~response to the position request, receive position information from the acquired GPS satellites and decode the received satellite information to generate decoded position information that requires processing to determine a position; and~~

~~wherein the GPS-enabled device further comprises a transmitter, wherein the GPS receiver is further configured to receive position information from the acquired GPS satellites and to decode the received position information, and wherein the GPS-enabled device is further configured to transmit the decoded position information to the base station.~~

52. (currently amended) The wireless communication system of claim 51, wherein the base station further comprises a another GPS receiver configured to acquire, and receive the GPS satellite information from, GPS satellites.

53. (original) The wireless communication system of claim 51, further comprising a position determination entity, wherein the base station further comprises a network interface configured to interface the base station with the position determination entity, and wherein the base station configured to receive the GPS satellite information from the position determination entity through the network interface.

54. (original) The wireless communication system of claim 51, wherein the base station further comprises a processor configured to process the GPS satellite information, and wherein the base station is configured to transmit the processed information.

55. (original) The wireless communication system of claim 51, wherein the base station further comprises a receiver configured to periodically receive registration requests from the GPS enabled device, and wherein the base station is configured to transmit the GPS satellite information in response to the registration request.

56. (original) The wireless communication system of claim 51, wherein the transmitted information includes at least one of access assist information and sensitivity assist information.

57. (original) The wireless communication system of claim 51, wherein the GPS enabled device further comprises a transmitter configured to periodically transmit a registration request to the base station, and wherein the GPS satellite information is received during the periodic registrations.

58. (cancelled)

59. (original) The wireless communication system of claim 51, wherein the GPS enabled device is further configured to adjust a correlation time based on the stored information in order to improve the chances of acquiring the GPS satellites.

60. (cancelled)

61. (previously presented) The wireless communication system of claim 51, wherein the base station further comprises a full position determination entity, and wherein the position determination entity is configured to determine the position from the decoded position information.

62. (previously presented) The wireless communication system of claim 51, wherein the base station further comprises a receiver, the receiver configured to receive the decoded position information from the GPS enabled device.

63. (original) The wireless communication system of claim 62, wherein the base station is further configured to determine a position of the GPS enabled device based on the decoded position information, and to transmit the determined position to the GPS enabled device.

64. (original) The wireless communication system of claim 62, further comprising a position determination entity, wherein the base station further comprises a network

interface configured to interface the base station with the position determination entity, the base station configured to:

- send the decoded position information to the position determination entity through the network interface;

- receive a position of the GPS enabled device determined from the decoded position information from the position determination entity through the network interface; and

- transmit the position to the GPS enabled device.

65. (original) The wireless communication system of claim 51, further comprising a control channel, wherein the GPS enabled device is configured to receive the GPS satellite information from the base station over the control channel.

66. (original) The wireless communication system of claim 65, wherein the control channel is a PCS common control channel.